AIRWORTHINESS REQUIREMENTS

TEMPORARY REVISION 2B–2238

The contents of this Temporary Revision have been approved by the Chief, Engineering (or designate), National Aircraft Certification Branch, Transport Canada Civil Aviation

Date 19 June, 2014 Signed Remy Knoerr

FILING INSTRUCTIONS: This Temporary Revision (TR) supersedes TR 2B–2224. Remove and discard TR 2B–2224 and insert this TR 2B–2238 facing page 2B–68, in Part 2 of the Maintenance Requirements Manual (MRM).

Record the incorporation of this Temporary Revision on the RECORD OF TEMPORARY REVISIONS sheet at the front of the MRM Part 2.

Keep this Temporary Revison until normal revision service incorporates this information into the Maintenance Requirements Manual.

DESCRIPTION: This Temporary Revision is issued to revise INSPECT TYPE and INTERVALS of AWL NUMBER 57–21–161.

Superseded TR 2B–2224 was issued to revise the EFFECTIVITY, INTERVALS and LIMITATION of AWL NUMBER 57–21–161.

AIRWORTHINESS REQUIREMENTS

TEMPORARY REVISION 2B–2238

STRUCTURAL AIRWORTHINESS LIMITATIONS

AWL NUMBER	MRB TASK REFERENCE	NDT MANUAL REF.	DESCRIPTION	INSPECT TYPE	INSPECTION INTERVAL			
					51000 lb MTOW		53000 lb MTOW	
					THRESHOLD (LANDINGS)	REPEAT (LANDINGS)	THRESHOLD (LANDINGS)	REPEAT (LANDINGS)
57–21–161	57–21–06–03	57–21–161 Part 6	MLG Mounting Trunnion Web at WS66 Pre SB 601R–57–046 or Pre SB 601R–57–048	Special Detailed NOTE4	25000 [1] 16667 [2]	3000 [1] 2000 [2]	25000 [1] 16667 [2]	3000 [1] 2000 [2]
		57–21–161 Part 9	CANADAIR PART NUMBER EFFECTIVITY: 601R10031–1 or 601R10031–2 or 601R10031–11 or 601R10031–12 or 601R10068–1 or 601R10068–2 or 601R10068–5 or 601R10068–6 or (601R10031–1 and In–Service Mod TC601R16268) or (601R10031–2 and In–Service Mod TC601R16268) LIMITATION: AWL is valid up to 34900 Flight Cycles. At or before 34900 Flight Cycles, the following actions shall be required: 1) Remove and Replace with Canadair Part Number 601R10068–5 and –6 if SB 601R–57–046 and SB601R–57–048 are not incorporated. After Part Replacement, AWL 57–21–155 and AWL 57–21–161 inspections and limitations still apply. (Continued on next page)	Detailed Visual NOTE 4	25000 [1] 16667 [2]	1500 [1] 1000 [2]	25000 [1] 16667 [2]	1500 [1] 1000 [2]

AIRWORTHINESS REQUIREMENTS

TEMPORARY REVISION 2B–2238

STRUCTURAL AIRWORTHINESS LIMITATIONS

AWL NUMBER	MRB TASK REFERENCE	NDT MANUAL REF.	DESCRIPTION	INSPECT TYPE	INSPECTION INTERVAL			
					51000 lb MTOW		53000 lb MTOW	
					THRESHOLD (LANDINGS)	REPEAT (LANDINGS)	THRESHOLD (LANDINGS)	REPEAT (LANDINGS)
			2) Next inspection required at 34900 Flight Cycles if SB 601R–57–048 is incorporated. SB 601R–57–046 shall be incorporated at or before 34900 flight cycles. [1] Pre Modsum TC601R15827 [2] Post Modsum TC601R15827 NOTE: Subject to TC AD action					